



[ABOUT](#) ▾

[FOREMOST ENERGY EQUIPMENT](#) ▾

[FOREMOST MOBILE EQUIPMENT](#) ▾

[PARTS & SERVICE](#) ▾

[CAREERS](#)

[CONTACT](#)

[Home](#) / [Foremost Mobile Equipment](#) / [Wheeled Vehicles](#) /

[Delta 3](#)

DELTA 3

Wheeled Carrier



The Foremost Delta 3 is a versatile all-wheel drive, terra-tired transporter. Utilizing proven powertrain components and heavy duty center-frame steering, this high floatation vehicle provides economic transportation of payloads up to 15 tons. The Delta 3 provides superior off-highway mobility and can be readily adapted for all chassis-mounted equipment. It is ideal for logistical support of remote drilling operations, pipeline and powerline construction and maintenance, or other specialized projects faced with travel through marginal terrain conditions.

OPTIONS

- ROP Canopy
 - Emergency Steering & Brake System
 - Recovery Winch
-

SPECIFICATIONS

Performance		
Payload	30,000 lbs	13,600 kg

Tare	29,300 lbs	13,300 kg
Gross Vehicle Weight	59,300 lbs	26,900 kg
Maximum Speed	20.3 mph	32.8 km/h
Fording Depth	4' 6"	1.37 m
Maximum Gradeability	Side 30%	Forward 50%
Ground Pressure at 3"		
Penetration		
0 tons	3.3 psi	22.9 kPa
5 tons	4.7 psi	32.5 kPa
10 tons	6.1 psi	42.1 kPa
15 tons	7.5 psi	51.6 kPa
Engine		
Make	Cat	
Model	C7	C9 (Optional)
Type	Diesel EPA Tier 4 Flex	
Cylinders	6	
Displacement	537 in ³	8.8 L
Horsepower @ 2100 RPM	325 hp	242 kW
Torque @ 1400 RPM	1,095 ft-lb	1,485 Nm
Drive Train		
Transmission	Funk DF 250. Full powershift with bi-directional PTO. Direct drive hydraulic steering pump. Front Axle disconnect.	
Differential	Kessler planetary drive. Metal face seals on planet hubs.	
Front Differential	Standard Spider	
Rear Differential	No Spin	
Suspension		
Front Undercarriage	Semi-elliptical, multi-leaf spring, full floating and stabilized by torque arms	
Rear Undercarriage	Rigidly mounted rear axle. Walking beam.	
Dimensions		
Length (3-man cab)	38.5'	11.7 m

Width	11' 4"	3.46 m
Height - Overall	10' 10"	3.3 m
Height - Rear of Frame	5'	1.52 m
Ground Clearance	21.5"	546 mm
Gage	7' 9"	2.36 m
Wheel Base	21' 4"	6.5 m
Tandem Spacing	6'	1.83 m
Optional Deck		
Length	20'	6.1 m
Width	8'	2.44 m
Electrical Systems		
	IQAN Control System	
Voltage	12V	
Alternator Capacity	145 A	
Battery Capacity	4 batteries, Delco 1151, 580 CCA	
Tires	Goodyear 66 x 43 x 25 Bias Ply	
Fuel Capacity	132 US Gal	500 L
Air Cleaner	Heavy duty dry type, with replaceable element	
Steering	Articulated frame for steering with self- aligning bushings. Steering wheel controlled.	
Brakes		
Parking	Internal Transmission SAHR Brake	
Service	Wet Disc Planetary Brakes	
Frame	High strength alloy steel welded	

GALLERY



VIDEO

DOWNLOADS



Foremost
Vehicles
Product
Overview



Delta
Product
Information

CONTACT

JIM FULTON

E-mail: jim.fulton@foremost.ca





Phone (Toll Free Canada/USA): 1-800-661-9190 ext: 805

Phone (worldwide): 1-403-295-5800

**EMPLOYEE
LOGIN**


Webmail
Employee News
Employee
Resources
New Employee
Orientation
Portal
Shop Foremost

**FOREMOST HEAD
OFFICE**

 6614 - 50
Avenue
Lloydminster AB, T9V
2W8
 1.800.661.9190
 info@foremost.ca
 **FAX:**
1.780.875.6169

**FOREMOST
LOCATIONS**

Serving all of
Western Canada &
Alberta with
locations in Calgary,
Edmonton, Grand
Prairie, Lloydminster
& Stettler



Quotes by [TradingView](#)