

**LOW IMPACT**



**HÄGGLUNDS BV206**



# LOW IMPACT

## HÄGGLUNDS BV206

THE HÄGGLUNDS BV206 IS THE MOST VERSATILE VEHICLE ON THE PLANET.

SNOW, MUD, MUSKEG OR SAND, THE CHASSIS IS PROVEN AND STILL UTILIZED BY THE MILITARY TODAY.

THIS AMAZING OFFROAD MACHINE IS ALSO AMPHIBIOUS. WITH THE ORIGINAL CABOOSE OR FLOATING FLATDECK - PROPELLED BY THE ARTICULATED TRACKS - THIS MACHINE CAN TRAVEL 4 KM/HR IN WATER.

CARRY A CREW UP TO 15 WHILE HAULING EQUIPMENT OF UP TO 4000 LBS. ACCESS REMOTE LOCATIONS SAFELY AND EFFICIENTLY.

### **YOUR ALL ACCESS PASS TO MOTHER NATURE**

ARTICULATED STEERING - FOUR TRACK DRIVE

ENGINEERED BY THE MILITARY

AUTOMATIC TRANSMISSION

HIGH SPEED

UNIQUE CROSS-COUNTRY CAPABILITY

MINIMUM DAMAGE TO THE GROUND SURFACE

SIMPLE TO OPERATE

RELIABLE ON THE JOB.

# LOW IMPACT

## HÄGGLUNDS BV206

### ***DIMENSIONS | WEIGHT***

**LENGTH** | 6.9 M OR 20.6 FT.

**WIDTH** | 1.9 M OR 6.2 FT

#### **HEIGHT**

FRONT CAR | 2.3 M OR 7.5 FT

REAR CAR | 2.5 M OR 8.2 FT

#### **CURB WEIGHT**

FRONT CAR | 2740 KG OR 6041 LBS

REAR CAR | 1610 KG OR 3549 LBS

#### **PAYLOAD**

FRONT CAR | 630 KG OR 1389 LBS

REAR CAR | 1610 KG OR 3549 LBS

#### **PASSENGERS**

FRONT CAR | 6 INCLUDING DRIVER

REAR CAR | 11

**MAX TRAILER WEIGHT** | 2500 KG OR 5512 LBS

**GROUND PRESSURE** | 1.26 PSI

YOUR ALL ACCESS PASS TO MOTHER NATURE.

# LOW IMPACT

## HÄGGLUNDS BV206

### PERFORMANCE

#### MAX SPEED

ROAD | 55 KM|HR OR 31 MPH

WATER | 4 KM|HR OR 2.5 MPH

#### GRADEABILITY

HARD SURFACE | 100% | 45°

DEEP SNOW | 30% | 17°

RANGE ON ROAD | 330 KM

#### OPERATING TEMPERATURE

MAX | 46°C OR 114.8 °F

MIN | -40°C OR -40°F

### ENGINE

MAKE | FORD GAS 2.8L COLOGNE - MANUFACTURED IN GERMANY

TRANSMISSION | MERCEDES BENZ OM 603.950

SWEPT VOLUME | 2996 CC [183 CU.IN]

POWER | 100 KW [136 HP] | 4600 RPM

TORQUE | 187 LB|FT [255 NM]

YOUR ALL ACCESS PASS TO MOTHER NATURE.



# LOW IMPACT

## HÄGGLUNDS BV206

### GEARBOX

MAKE | MERCEDES BENZ W4A-040

TYPE | AUTOMATIC 4 SPEED FORWARD | 1 REVERSE

TRANSFER GEARBOX MAKE | HÄGGLUNDS VEHICLE AB

### GEAR RATIOS

HIGH | 1:28:1

LOW | 2:11:1

### STEERING SYSTEM

TYPE | HYDROSTATIC | ARTICULATED

SWEPT DIAMETER | 16 M OR 52.5 FT

EMERGENCY STEERING | STANDARD

### TRACKS

TYPE | MOLDED RUBBER WITH CORD

WIDTH | 0.6 M OR 2 FT

YOUR ALL ACCESS PASS TO MOTHER NATURE.

# LOW IMPACT

## HÄGGLUNDS BV206

### *ELECTRICAL SYSTEM*

**VOLTAGE** | 24V DC

**ALTERNATOR** | 100 AMP

**BATTERY** | 105 AH | 2X12 V

### *BODIES*

#### **MATERIAL**

REINFORCED FIBRE GLASS

PVC PLASTIC

FOAM INSULATION

YOUR ALL ACCESS PASS TO MOTHER NATURE.